

APPLICATIONS CHART

Plasma Cutters

Standard Pressure 0 - 10KSI



| Target Pipe OD | Target Pipe Wt (ID) | Complete Tool P/N | Recommended Plasma Cutter OD |
|----------------|--|-------------------|------------------------------|
| 1-1/2" CT | 1.426 - 1.957 lb/ft (1.241" - 1.317") | C-0875-1500-2 | 7/8" OD |
| 1-3/4" CT | 1.912 - 3.139 lb/ft (1.388" - 1.540") | C-0875-1750-3 | |
| 2-3/8" CT | 3.7 - 5.396 lb/ft (1.903" - 2.063") | C-1500-2375-2 | 1-1/2" OD |
| 2-3/8" TBG | 4.7 - 5.95 lb/ft (1.876" - 1.995") | C-1500-2375-2 | |
| | 6.2 - 7.7 lb/ft (1.703" - 1.853") | C-1500-2375-3 | |
| 2-5/8" CT | 3.844 - 5.749 lb/ft (2.177" - 2.335") | C-1500-2625-2 | |
| 2-7/8" TBG | 6.5 - 7.9 lb/ft (2.323" - 2.441") | C-1500-2875-4 | |
| | 8.7 - 10.7 lb/ft (2.059" - 2.262") | C-1500-2875-5 | |
| 3-1/2" TBG | 9.3 - 12.95 lb/ft (2.750 - 2.992") | CW-1500-3500-5 | 1-1/2" OD CW* |
| | 9.3 - 12.95 lb/ft (2.750 - 2.992") | C-2000-3500-3 | 2" OD |
| | 13.3 - 16.7 lb/ft (2.480" - 2.762") | C-2000-3500-4 | |
| 4" TBG | 9.5 - 14 lb/ft (3.340" - 3.548") | C-2000-4000-4 | 2" OD CW* |
| 4-1/2" TBG | 9.5 - 13.5 lb/ft (3.920" - 4.090") | CW-2000-4500-8 | |
| | 9.5 - 13.5 lb/ft (3.920" - 4.090") | C-2500-4500-3 | |
| | 15.1 - 16.6 lb/ft (3.773" - 3.845") | C-2500-4500-4 | |
| 5" DP | 16.25 - 21.4 lb/ft (4.153" - 4.372") | CW-2500-5000-8 | 2-1/2" OD CW* |
| | 16.25 - 21.4 lb/ft (4.153" - 4.372") | C-2750-5000-8 | 2-3/4" OD |
| | 23.2 - 24.1 lb/ft (4.034" - 4.074") | C-2750-5000-9 | |
| 5-1/2" DP | 17-23 lb/ft (4.67" - 4.892") | CW-2500-5500-9 | 2-1/2" OD CW* |
| | 17-23 lb/ft (4.67" - 4.892") | CW-3500-5500-7 | 3-1/2" OD |

*CW: UNDERSIZED CUTTER