



CHAMMAS PLASMA CUTTERS

APPLICATIONS CHART

Plasma Cutters
High Pressure 10 - 15KSI



Target Pipe OD	Target Pipe Wt (ID)	Complete Tool P/N	Recommended Plasma Cutter OD
2-3/8" CT	3.7 - 5.396 lb/ft (1.903" - 2.063")	C-1500-2375-X	1-1/2" OD
2-3/8" TBG	4.7 - 5.95 lb/ft (1.876" - 1.995")	C-1500-2375-6	
	6.2 - 7.7 lb/ft (1.703" - 1.853")	C-1500-2375-7	
2-5/8" CT	3.844 - 5.749 lb/ft (2.177" - 2.335")	C-1500-2625-X	
2-7/8" TBG	6.5 - 7.9 lb/ft (2.323" - 2.441")	C-1500-2875-10	
	8.7 - 10.7 lb/ft (2.059" - 2.262")	C-1500-2875-11	
3-1/2" TBG	9.3 - 12.95 lb/ft (2.750 - 2.992")	CW-1500-3500-X	1-1/2" OD CW*
	9.3 - 12.95 lb/ft (2.750 - 2.992")	C-2000-3500-9	2" OD
	13.3 - 16.7 lb/ft (2.480" - 2.762")	C-2000-3500-10	
4" TBG	9.5 - 14 lb/ft (3.340" - 3.548")	C-2000-4000-10	
4-1/2" TBG	9.5 - 13.5 lb/ft (3.920" - 4.090")	CW-2000-4500-X	2" OD CW*
	9.5 - 13.5 lb/ft (3.920" - 4.090")	C-2500-4500-9	2-1/2" OD
	15.1 - 16.6 lb/ft (3.773" - 3.845")	C-2500-4500-10	
5" DP	16.25 - 21.4 lb/ft (4.153" - 4.372")	CW-2500-5000-X	2-1/2" OD CW*
	16.25 - 21.4 lb/ft (4.153" - 4.372")	C-2750-5000-X	2-3/4" OD
	23.2 - 24.1 lb/ft (4.034" - 4.074")	C-2750-5000-X	

***CW: UNDERSIZED CUTTER**